

SAFETY DATA SHEET

May be used to comply with OSHA Hazcom 29 CFR 1910.1200. Standards must be consulted for specific requirements.

Revision Date: 2019-02-18

1. IDENTIFICATION

Product Name: Statguard® Conductive Acrylic Paint, Light Grey

Identified use: Acrylic Paint

Company Identification: DESCO INDUSTRIES INC

One Colgate Way
Canton, MA 02021
UNITED STATES
+1 781-821-8370

Email Address: Service@DescolIndustries.com

Emergency telephone number

United States: +1 781-821-8370

Office hours: 8:00 AM - 5:00 PM

2. HAZARDS IDENTIFICATION

Hazard classification

This material is hazardous under the criteria of the Federal OSHA Hazcom 29 CFR 1910.1200.

Acute Toxicity (Oral)	Category 4
Skin Irritation	Category 2
Eye Irritation	Category 2A
Skin Sensitisation	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 1
Specific target organ toxicity (Repeated exposure)	Category 2

Label elements

Hazard pictograms/Symbols:



Signal word:

WARNING

Hazard statements:

Harmful if swallowed.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
May cause cancer.
May damage fertility or the unborn child.
May cause damage to organs through prolonged or repeated exposure.

Precautionary statements:

Prevention

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Avoid breathing dust/fume/gas/mist/vapors/spray.
Wash hand/skin thoroughly after handling.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves/protective clothing/eye protection/face protection.

Response

IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

IF ON SKIN: Wash with plenty of water.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

IF exposed or concerned: Get medical advice/attention.

Get medical advice/attention if you feel unwell.

Specific treatment (see on this label).

Rinse mouth.

If skin irritation or rash occurs: Get medical advice/attention.

If eye irritation persists: Get medical advice/attention.

Take off contaminated clothing and wash it before reuse.

Wash contaminated clothing before reuse.

Storage

Store locked up.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

3. COMPOSITION/INFORMATION ON INGREDIENTS

This product is a mixture.

Components	CAS No.	Concentration
Trade Secret (Epoxy Ester)		10 - 25 %
2-butoxyethanol	111-76-2	2.5 - 10 %
Mica - Potassium Aluminum Silicate	12001-26-2	2.5 - 10 %
Tin Antimony Oxide	68187-54-2	2.5 - 10 %
Quartz (SiO ₂)	14808-60-7	2.5 - 10 %
Titanium dioxide	13463-67-7	2.5 - 10 %
Butan-1-ol	71-36-3	0.1 - 2.5 %
Cobalt bis(2-ethylhexanoate)	136-52-7	0.1 - 2.5 %
Manganese Carboxylate	84-74-2	0.1 - 2.5 %
Dibutyl phthalate	15956-58-8	0.1 - 1.0 %

4. FIRST AID MEASURES**Description of first aid measures****General advice:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Inhalation:

Supply fresh air and to be sure call for a doctor. In case of unconsciousness place patient stably in side position for transportation.

Skin Contact

In case of contact, immediately wash with water and soap and rinse thoroughly.

Eye Contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Ingestion

If symptoms persist consult doctor. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

Indication of any immediate medical attention and special treatment needed

Notes to physician: No specific antidote. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

5. FIREFIGHTING MEASURES

Extinguishing media

Suitable Extinguishing Media CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable Extinguishing Methods None known

Special hazards arising from the substance or mixture

No further relevant information available.

Unusual Fire and Explosion Hazards: None known.

Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Contain fire water run-off if possible.

Special protective equipment for firefighters: Wear self-contained breathing apparatus and protective suit. If protective equipment is not available or not used, fight fire from a protected location or safe distance.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Use personal protective equipment. Keep people away from and upwind of spill/leak. Material can create slippery conditions.

Environmental precautions

Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.

Methods and materials for containment and cleaning up

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to SECTION 13.

Reference to other sections

See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.

Protective Action Criteria for Chemicals

PAC-1:

Hazardous Ingredients	CAS No.	Rating
2-butoxyethanol	111-76-2	60 ppm
Mica - Potassium Aluminum Silicate	12001-26-2	9 mg/m ³
Quartz (SiO ₂)	14808-60-7	0.075 mg/m ³
Titanium dioxide	13463-67-7	30 mg/m ³
Butan-1-ol	71-36-3	60 ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	126-86-3	30 mg/m ³
1-methoxy-2-propanol	107-98-2	100 ppm
Poly(propylene glycol)	25322-69-4	30 mg/m ³
Dibutyl phthalate	84-74-2	15 mg/m ³
Stoddard solvent	8052-41-3	300 mg/m ³

PAC-2:

Hazardous Ingredients	CAS No.	Rating
2-butoxyethanol	111-76-2	120 ppm
Mica - Potassium Aluminum Silicate	12001-26-2	99 mg/m ³
Quartz (SiO ₂)	14808-60-7	33 mg/m ³
Titanium dioxide	13463-67-7	330 mg/m ³
Butan-1-ol	71-36-3	800 ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	126-86-3	330 mg/m ³
1-methoxy-2-propanol	107-98-2	160 ppm
Poly(propylene glycol)	25322-69-4	330 mg/m ³
Dibutyl phthalate	84-74-2	1,600 mg/m ³
Stoddard solvent	8052-41-3	1,800 mg/m ³

PAC-3:

Hazardous Ingredients	CAS No.	Rating
2-butoxyethanol	111-76-2	700 ppm
Mica - Potassium Aluminum Silicate	12001-26-2	590 mg/m ³
Quartz (SiO ₂)	14808-60-7	200 mg/m ³
Titanium dioxide	13463-67-7	2,000 mg/m ³
Butan-1-ol	71-36-3	8,000** ppm
2,4,7,9-tetramethyldec-5-yne-4,7-diol	126-86-3	2,000 mg/m ³
1-methoxy-2-propanol	107-98-2	660 ppm
Poly(propylene glycol)	25322-69-4	2,000 mg/m ³
Dibutyl phthalate	84-74-2	9,300* mg/m ³
Stoddard solvent	8052-41-3	29,500** mg/m ³

7. HANDLING AND STORAGE**Precautions for safe handling**

Avoid contact with eyes, skin and clothing. Wash thoroughly after handling. Keep container tightly closed. Do not breathe vapors, mist or gas.

Conditions for safe storage, including any incompatibilities

Keep from freezing - product stability may be affected. For commercial and industrial use only.

Storage stability

Storage temperature: 1°C - 49°C (34°F - 120°F)

See SECTION 8, for types of ventilation required.

8. EXPOSURE CONTROL / PERSONAL PROTECTION**Control parameters****Components with limit values that require monitoring at the workplace:**

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the other constituent have no known exposure limits.

2-butoxyethanol (CAS No.: 111-76-2)	
PEL	Long-term value: 240 mg/m ³ , 50 ppm Skin
REL	Long-term value: 24 mg/m ³ , 5 ppm Skin
TLV	Long-term value: 97 mg/m ³ , 20 ppm BEI

Mica - Potassium Aluminum Silicate (CAS No.: 12001-26-2)

PEL	Long-term value: 20 mppcf ppm <1% crystalline silica
REL	Long-term value: 3* mg/m ³ *respirable dust; containing < 1% quartz
TLV	Long-term value: 3* mg/m ³ *as respirable fraction

Quartz (SiO₂) (CAS No.: 14808-60-7)

PEL	see Quartz listing
REL	Long-term value: 0.05* mg/m ³ *respirable dust; See Pocket Guide App. A
TLV	Long-term value: 0.025* mg/m ³ *as respirable fraction

Butan-1-ol (CAS No.: 71-36-3)

PEL	Long-term value: 300 mg/m ³ , 100 ppm
REL	Ceiling limit value: 150 mg/m ³ , 50 ppm Skin
TLV	Long-term value: 61 mg/m ³ , 20 ppm

Cobalt bis(2-ethylhexanoate) (CAS No.: 136-52-7)

TLV	Long-term value: (0.02) NIC-0.02* mg/m ³ as Co, *inhalable; NIC-Skin,DSEN,RSEN,(BEI)
-----	--

Dibutyl phthalate (CAS No.: 84-74-2)

PEL	Long-term value: 5 mg/m ³
REL	Long-term value: 5 mg/m ³
TLV	Long-term value: 5 mg/m ³

Ingredients with biological limit values:**2-butoxyethanol (CAS No.: 111-76-2)**

BEI	200 mg/g creatinine Medium: urine Time: end of shift Parameter: Butoxyacetic acid with hydrolysis
-----	--

Additional information: The lists that were valid during the creation were used as basis.

Exposure controls

Technical Control: Use local exhaust, or other technology solutions to keep air levels below given or recommended limit values. If limit values are not present, good general ventilation should be sufficient. Local exhaustion may be required in some operations.

Individual protection measures**Protective Gloves**

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.
Due to missing tests, no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation.

Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection

Use tightly sealed goggles.

General protective and Hygienic Practices

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing.
Wash hands before breaks and at the end of work.
Avoid contact with the eyes and skin.

9. PHYSICAL AND CHEMICAL PROPERTIES**Information on basic physical and chemical properties**

Appearance:	Liquid
Color:	Light grey
Odor:	Characteristic
Odor Threshold:	N/A
pH:	8.2 - 8.8
Melting Point:	N/A
Boiling Point:	100 °C (212 °F)
Flash Point:	94 °C (201 °F)
Ignition temperature	240 °C (464 °F)
Evaporation rate:	Slower than (n-Butyl Acetate)
Flammability:	N/A
Upper flammability or explosive limits:	N/A
Lower flammability or explosive limits:	N/A
Vapor Pressure @ 20°C (68°F):	17 mm Hg or 23hPa
Vapor Density (air=1):	Heavier than air
Relative Density:	N/A
Density @ 20°C (68°F):	1.182 g/cm ³ (9.864 lbs/gal)
Specific Gravity (H ₂ O = 1) :	N/A
Solubility:	Fully miscible.
Partition coefficient:	N/A
Auto-ignition temperature:	Product is not selfigniting.
Decomposition temperature:	N/A
Dynamic viscosity:	N/A
Kinematic viscosity:	24 - 28s (#3 Zayn cup)
Explosive properties:	Product does not present an explosion hazard
Oxidizing properties:	N/A
VOC Content:	124.3 g/l / 1.04 lb/gl
Solids Content:	33 - 37%

Other information

Surface Resistance ≤ 1x10E4 ohms

10. STABILITY AND REACTIVITY

Reactivity: No further relevant information available.

Chemical stability: No decomposition if used according to specifications.

Possibility of hazardous reactions: No dangerous reactions known.

Conditions to avoid: No further relevant information available.

Incompatible materials: No further relevant information available.

Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11 — TOXICOLOGICAL INFORMATION**11.1 Information on toxicological effects****Acute Effects:**

Eye Contact Irritating effect.

Skin Contact Irritant to skin and mucous membranes.
 Sensitization Sensitization possible through skin contact.
 Additional toxicological info. The product shows the following dangers according to internally approved calculation methods for preparations:
 Irritant & Harmful

Carcinogenic Categories:

	Chemical	CAS#	Rating
IARC (International Agency for Research on Cancer)	2-butoxyethanol	111-76-2	3
	Quartz (SiO2)	14808-60-7	1
	Titanium dioxide	13463-67-7	2B
	Cobalt bis(2-ethylhexanoate)	136-52-7	2B
NTP (National Toxicology Program)	Quartz (SiO2)	14808-60-7	K
OSHA-Ca (Occupational Safety & Health Administration)	No ingredient of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.		

12. ECOLOGICAL INFORMATION

Ecotoxicological information appears in this section when such data is available.

Toxicity

Aquatic toxicity: No further relevant information available.

Persistence and degradability: No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential: No further relevant information available.

Mobility in soil: No further relevant information available.

Additional ecological information:

General notes:

Water hazard class 1 (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Results of PBT and vPvB assessment

PBT: Not applicable.

vPvB: Not applicable.

Other adverse effects: No further relevant information available.

13. DISPOSAL CONSIDERATIONS

Disposal methods

Product Any disposal practices must be in compliance with all national and provincial laws and any municipal or local by-laws governing hazardous waste. For used, contaminated and residual materials additional evaluations may be required. Do not dump into any sewers, on the ground, or into any body of water.

14. TRANSPORT INFORMATION

DOT (Department of Transportation) Not regulated for transport
 Classification for SEA transport (IMO-IMDG) Not regulated for transport
 Consult IMO regulations before transporting ocean bulk.
 Classification for AIR transport (IATA/ICAO) Not regulated for transport

15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

SARA Title III Inventory of the Emergency Planning and Community Right-To-Know Act of 1986 and of 40

